

D25P33E4GL00LF

a Quote

D25P33E4GL00LF Information

Heisener.com	Part Number	D25P33E4GL00LF	
	Manufacturer	Amphenol FCI	同時五
	Category	Connectors, Interconnects D-Sub Connectors	
	Description	CONN D-SUB PLUG 25POS R/A SOLDER	
	Package	-	- F.A
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D25P33E4GL00LF Specifications

Manufacturer Amphenol FCI Connectors, Interconnects D-Sub Connectors Package - Package Delta D Connector Style D-Sub Connectors Connector Style Plug, Male Pins Connector Style 25 Number of Positions 2 Shell Size, Connector Layout 3 (DB, B) Contact Type Signal Mounting Type Through Hole, Right Angle Plange Feature Solder Shell Material, Finish Steel, Tin Plated Contact Finish Thickness Flash Spenter Finish Thickness Flash Contact Finish Thickness UL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleParinationSolderFerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	D25P33E4GL00LF
D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsConnector Type25Number of Positions2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureHousing/Shell (M3)FerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashAuterial Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalContact TypeHousing/Shell (M3)Pange FeatureHousing/Shell (M3)FerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashContact Finish ThicknessFlashAuterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlanshContact Finish ThicknessFlashMaterial Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalContact TypeThrough Hole, Right AngleMounting TypeSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashAuterial Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (M3)SolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Series	Delta D
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (M3)SolderFerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough Hole, Right AngleFange FeaturesHousing/Shell (M3)FeaturesSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (M3)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

D25P33E4GL00LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D25P33E4GL00LF Payment Methods



D25P33E4GL00LF Shipping Methods



If you have any question about D25P33E4GL00LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com