

D25P80C6GX00LF

a Quote

D25P80C6GX00LF Information

Heisener.com	Part Number	D25P80C6GX00LF	
	Manufacturer	Amphenol FCI	E 153
	Category	Connectors, Interconnects D-Sub Connectors	
	Description	CONN D-SUB PLUG 25POS R/A PRESS	_ <u>254</u>
	Package	-	- Six
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D25P80C6GX00LF Specifications

ManufacturerAmphenol FCICategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-Sub ConnectorConnector TypePlug, Male PinsConnector Type2Number of Positions2Shell Size, Connector LayoutSignalContact TypeSignalMounting TypeFlousgi/Shell (4-40)Flange FeatureBoard Guide, Grounding IndentsFeaturesSored Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessJuju (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeHousing/Shell (4-40)Flange FeatureBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	D25P80C6GX00LF
D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeMuonting TypeHousing/Shell (4-40)Press-FitFlange FeatureBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Shell Size, Connector LayoutSignalMounting TypeThrough Hole, Right AngleFlange FeaturePress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessSoupin (0.76µm)Ingress Protection-	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Guide, Grounding IndentsFeaturesSteel, Tin PlatedShell Material, FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	Delta D
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeaturesHousing/Shell (4-40)TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureHousing/Shell (4-40)TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationPress-FitFeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Guide, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Press-Fit
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Guide, Grounding Indents
Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

D25P80C6GX00LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D25P80C6GX00LF Payment Methods



D25P80C6GX00LF Shipping Methods



If you have any question about D25P80C6GX00LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com