



D25S90C6GV00 Information

Heisener.com

Part Number D25S90C6GV00 Manufacturer Amphenol FCI

Category Connectors, Interconnects

D-Sub Connectors

Description CONN D-SUB RCPT 25POS VERT PRESS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D25S90C6GV00 Specifications

Manufacturer Part Number Manufacturer Amphenol FCI Category Connectors, Interconnects D-Sub Connectors Package - Series Delta D Connector Style Connector Type Receptacle, Female Sockets Number of Positions 25 Number of Rows 2 Shell Size, Connector Layout Signal Mounting Type Through Hole Flange Feature Mating Side, Female Screwlock (4-40) Termination Press-Fit Features Board Lock Shell Material, Finish Contact Finish Contact Finish Contact Finish Thickness Jojin (0.76µm) Ingress Protection Material Flammability Rating UL94 V-0 Report errors?	î de la companya de	
Category Connectors, Interconnects D-Sub Connectors Package - Series Delta D Connector Style Connector Type Receptacle, Female Sockets Number of Positions 25 Number of Rows 2 Shell Size, Connector Layout 3 (DB, B) Contact Type Signal Mounting Type Through Hole Flange Feature Mating Side, Female Screwlock (4-40) Termination Press-Fit Features Board Lock Shell Material, Finish Contact Finish Gold Contact Finish Gold Contact Finish Thickness Ingress Protection - Material Flammability Rating UL94 V-0	Manufacturer Part Number	D25S90C6GV00
Package - Delta D Connector Style D-Sub Connector Type Receptacle, Female Sockets Number of Positions 25 Number of Rows 2 Shell Size, Connector Layout 3 (DB, B) Contact Type Signal Mounting Type Through Hole Flange Feature Mating Side, Female Screwlock (4-40) Termination Press-Fit Features Board Lock Shell Material, Finish Steel, Tin Plated Contact Finish Thickness 30µin (0.76µm) Ingress Protection Material Flammability Rating UL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	Delta D
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
Termination Press-Fit Features Board Lock Shell Material, Finish Steel, Tin Plated Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Ingress Protection - Material Flammability Rating UL94 V-0	Mounting Type	Through Hole
FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Press-Fit
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock
Contact Finish Thickness 30μin (0.76μm) Ingress Protection - Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30μin (0.76μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
X.		Report errors?

D25S90C6GV00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D25S90C6GV00 Payment Methods

































If you have any question about D25S90C6GV00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com