

D3044 Information

www.festerner.co

For Reference Only

Part Number D3044

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D3044 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Relays Signal Relays, Up to 2 Amps Package - Series FP2, AXICOM Relay Type Telecom Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage (Max) 4.5 VDC
Category Relays Signal Relays, Up to 2 Amps Package - Series FP2, AXICOM Relay Type Telecom Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Package - Series FP2, AXICOM Relay Type Telecom Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Package - Series FP2, AXICOM Relay Type Telecom Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Series FP2, AXICOM Relay Type Telecom Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Relay Type Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Type Latching, Single Coil Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Current 16.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Contact Rating (Current) Switching Voltage 2A 250VAC, 220VDC - Max
Switching Voltage 250VAC, 220VDC - Max
Turn On Voltage (May)
Turn On Voltage (Max) 4.5 VDC
Turn Off Voltage (Min) -
Operate Time 20ms
Release Time 20ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors

D3044 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D3044 Payment Methods



















D3044 Shipping Methods













If you have any question about D3044, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com