

D3205 Information



For Reference Only

Part Number D3205

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part NumberD3205ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesFX2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current23.3mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4ms
Category Relays Signal Relays, Up to 2 Amps Package - Series FX2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 23.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 0.6 VDC
Signal Relays, Up to 2 Amps Package - Series FX2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 23.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Package - Series FX2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 23.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Series FX2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 23.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Relay TypeTelecomCoil TypeNon LatchingCoil Current23.3mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDC
Coil TypeNon LatchingCoil Current23.3mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDC
Coil Current 23.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC
Turn Off Voltage (Min) 0.6 VDC
Operate Time 4ms
Release Time 3ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

D3205 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D3205 Payment Methods





















D3205 Shipping Methods













If you have any question about D3205, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com