

Heisener.com

D3425 Information

Part Number D3425

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 9V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D3425 Specifications

Manufacturer Part NumberD3425ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysFackage-SeriesFT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current22.2mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesFT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current22.2mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	D3425
Package-SeriesFT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current22.2mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series FT2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 22.2mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesFT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current22.2mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current22.2mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 22.2mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Series	FT2, AXICOM
Coil Current Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	Telecom
Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Release Time - Mounting Type Through Hole Termination Style	Coil Current	22.2mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	9VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features - Mounting Type Through Hole Termination Style 6.75 VDC 6.75 VDC 6.75 VDC 6.75 VDC 6.75 VDC 5ms Fms Fms Fms Fms Fms Fms Fms	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style Description: Turn Off Voltage (Min) 5ms 5ms Features - Mounting Type Through Hole PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	6.75 VDC
Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.9 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
•	Mounting Type	Through Hole
D ()	Termination Style	PC Pin
Report errors?		Report errors?

D3425 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D3425 Payment Methods



















D3425 Shipping Methods













If you have any question about D3425, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com