

### **D3522N Information**

Heisener.com

Part Number D3522N

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

**Description RELAY TELECOM DPDT 2A 4.5V** 

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **D3522N Specifications**

Manufacturer Part Number     D3522N       Manufacturer     TE Connectivity Potter & Brumfield Relays       Category     Relays       Signal Relays, Up to 2 Amps       Package     -       Series     FU2, AXICOM       Relay Type     Telecom       Coil Type     Non Latching       Coil Current     44.4mA       Coil Voltage     4.5VDC       Contact Form     DPDT (2 Form C)       Contact Rating (Current)     2A       Switching Voltage     250VAC, 220VDC - Max       Turn On Voltage (Max)     3.38 VDC       Turn Off Voltage (Min)     0.45 VDC       Operate Time     5ms       Release Time     5ms       Features     -       Mounting Type     Surface Mount       Termination Style     Gull Wing    Report errors?		
Category         Relays           Package         -           Series         FU2, AXICOM           Relay Type         Telecom           Coil Type         Non Latching           Coil Current         44.4mA           Coil Voltage         4.5VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         250VAC, 220VDC - Max           Turn On Voltage (Max)         3.38 VDC           Turn Off Voltage (Min)         0.45 VDC           Operate Time         5ms           Release Time         5ms           Features         -           Mounting Type         Surface Mount           Termination Style         Gull Wing	Manufacturer Part Number	D3522N
Package-SeriesFU2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series FU2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Category	Relays
SeriesFU2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features Mounting Type Surface Mount Termination Style Guil Wing	Series	FU2, AXICOM
Coil Current Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.38 VDC  Turn Off Voltage (Min)  0.45 VDC  Operate Time  5ms  Release Time  5ms  Release Time  5ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Current	44.4mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.38 VDC  Turn Off Voltage (Min)  0.45 VDC  Operate Time  5ms  Release Time  5ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Voltage	4.5VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 3.38 VDC  Turn Off Voltage (Min) 0.45 VDC  Operate Time 5ms  Release Time 5ms  Features -  Mounting Type Surface Mount  Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  - Mounting Type  Surface Mount  Termination Style  3.38 VDC  3.38 VDC  5ms  5ms  6ms  6ms  6ms  6ms  6ms  6ms	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	3.38 VDC
Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.45 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	5ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	5ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

### **D3522N Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **D3522N Payment Methods**



















### **D3522N Shipping Methods**













If you have any question about D3522N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com