

D3529N Information

Heisener.com

Part Number D3529N

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

RELAY TELECOM DPDT 2A 4V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D3529N Specifications

Manufacturer Part Number D3529N Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Package - Series FU2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 50mA Coil Voltage 4VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing		
CategoryRelaysPackage-SeriesFU2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage4VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3 VDCTurn Off Voltage (Min)0.4 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	D3529N
Package-SeriesFU2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage4VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3 VDCTurn Off Voltage (Min)0.4 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesFU2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage4VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3 VDCTurn Off Voltage (Min)0.4 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesFU2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage4VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3 VDCTurn Off Voltage (Min)0.4 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage4VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3 VDCTurn Off Voltage (Min)0.4 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil Type Non Latching Coil Current 50mA Coil Voltage 4VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 5ms Release Time 5ms Features Mounting Type Surface Mount Termination Style Guil Wing	Series	FU2, AXICOM
Coil Current50mACoil Voltage4VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3 VDCTurn Off Voltage (Min)0.4 VDCOperate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Relay Type	Telecom
Coil Voltage 4VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 5ms Release Time 5ms Features Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style	Coil Current	50mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	4VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features - Mounting Type Surface Mount Termination Style 3 VDC 5ms 5ms 6ms 6ms 6ms 6ms 6ms 6mll Wing	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	3 VDC
Release Time 5ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.4 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	5ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	5ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

D3529N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D3529N Payment Methods





















D3529N Shipping Methods













If you have any question about D3529N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com