

D37P13A4GX00LF

Quote

D37P13A4GX00LF Information

| Heisener.com | Part Number | D37P13A4GX00LF | |
|--------------------|--------------|---|-----------|
| | Manufacturer | Amphenol FCI | 同的私 |
| | Category | Connectors, Interconnects D-Sub Connectors | |
| | Description | CONN D-SUB PLUG 37POS R/A SOLDER | |
| | Package | - | - 8330 |
| | | For the pricing/inventory/lead time, please contact | |
| For Reference Only | | us Website: https://www.heisener.com | Request a |
| | | E-mail: salesdept@heisener.com | 1 |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D37P13A4GX00LF Specifications

| D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | | |
|---|------------------------------|--|
| CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Manufacturer Part Number | D37P13A4GX00LF |
| PackageD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashMaterial Flammability RatingUL94 V-0 | Manufacturer | Amphenol FCI |
| Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)Shell Material, FinishStel, Tin PlatedContact FinishGoldContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Category | Connectors, Interconnects |
| SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | | D-Sub Connectors |
| Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Package | - |
| Connector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Series | Delta D |
| Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0 | Connector Style | D-Sub |
| Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Connector Type | Plug, Male Pins |
| Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Number of Positions | 37 |
| Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish FinishFlashIngress Protection-Material Flammability RatingUL94 V-0 | Number of Rows | 2 |
| Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Shell Size, Connector Layout | 4 (DC, C) |
| Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Contact Type | Signal |
| TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Mounting Type | Through Hole, Right Angle |
| FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Flange Feature | Housing/Shell (4-40) |
| Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Termination | Solder |
| Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Features | Board Lock, Grounding Indents, Mounting Brackets |
| Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Shell Material, Finish | Steel, Tin Plated |
| Ingress Protection-Material Flammability RatingUL94 V-0 | Contact Finish | Gold |
| Material Flammability Rating UL94 V-0 | Contact Finish Thickness | Flash |
| | Ingress Protection | - |
| Demonstrations? | Material Flammability Rating | UL94 V-0 |
| Report errors? | | Report errors? |

D37P13A4GX00LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D37P13A4GX00LF Payment Methods



D37P13A4GX00LF Shipping Methods



If you have any question about D37P13A4GX00LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com