

D37P13A6GX00LF

D37P13A6GX00LF Information

Heisener.com	 D37P13A6GX00LF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 37POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D37P13A6GX00LF Specifications

Manufacturer Amphenol FCI Connectors, Interconnects D-Sub Connectors Package - Series Delta D Connector Style D-Sub Connectors Connector Style D-Sub Connectors Connector Style Delta D Connector Type Plug, Male Pins Number of Positions 37 Shell Size, Connector Layout 4 (DC, C) Contact Type Signal Mounting Type Through Hole, Right Angle Flange Feature Board Lock, Grounding Indents, Mounting Brackets Shell Material, Finish Steel, Tin Plated Contact Finish Thickness Gold or Gold, GXT? Ingress Protection -		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFhrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	D37P13A6GX00LF
D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJUE94 V-0	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (4-40)SolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	Delta D
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	37
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeaturesHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish ThicknessJupin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold or Gold, GXT?
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

D37P13A6GX00LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D37P13A6GX00LF Payment Methods



D37P13A6GX00LF Shipping Methods



If you have any question about D37P13A6GX00LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com