



### D38999/20FH53PC Information

Heisener.com

Part Number D38999/20FH53PC

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 53POS FLANGE W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## D38999/20FH53PC Specifications

| Manufacturer Part Number     D38999/20FH53PC       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series III, DTS       Connector Type     Receptacle, Male Pins       Number of Positions     53       Shell Size - Insert     23-53       Shell Size, MIL     H       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Threaded       Orientation     C       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     7.5A |                          |   |
|--|--------------------------|---|
| Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A   | Manufacturer Part Number | D38999/20FH53PC                         |
| Circular Connectors  Package Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions S3 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A  | Manufacturer             | TE Connectivity Deutsch Connectors      |
| Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A   | Category                 | Connectors, Interconnects               |
| Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A   |                          | Circular Connectors                     |
| Connector TypeReceptacle, Male PinsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A   | Package                  | -                                       |
| Number of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A  | Series                   | Military, MIL-DTL-38999 Series III, DTS |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  C  Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  7.5A  | Connector Type           | Receptacle, Male Pins                   |
| Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A   | Number of Positions      | 53                                      |
| Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Threaded  Orientation C  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated  Contact Finish Gold  Features Shielded  Voltage - Rated -  Current Rating 7.5A   | Shell Size - Insert      | 23-53                                   |
| Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A  | Shell Size, MIL          | Н                                       |
| Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A  | Mounting Type            | Panel Mount, Flange                     |
| Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A  | Termination              | Crimp                                   |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A  | Fastening Type           | Threaded                                |
| Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Aluminum, Nickel Plated  Gold  Cold  Shielded   | Orientation              | C                                       |
| Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 7.5A   | Ingress Protection       | Environment Resistant                   |
| Features Shielded  Voltage - Rated - Current Rating 7.5A   | Shell Material, Finish   | Aluminum, Nickel Plated                 |
| Voltage - Rated - Current Rating 7.5A  | Contact Finish           | Gold                                    |
| Current Rating 7.5A  | Features                 | Shielded                                |
| -  | Voltage - Rated          | -                                       |
| Report errors?   | Current Rating           | 7.5A                                    |
|  |                          | Report errors?                          |

### D38999/20FH53PC Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## D38999/20FH53PC Payment Methods



















# D38999/20FH53PC Shipping Methods













If you have any question about D38999/20FH53PC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com