

D38999/20JJ35HA

Quote

D38999/20JJ35HA Information

Heisener.com	Manufacturer Category Description	D38999/20JJ35HA Souriau Connectors, Interconnects Circular Connectors CONN RCPT WALL MNT 128POS W/PIN	
	Package	- For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	•**
For Reference Only		E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D38999/20JJ35HA Specifications

ManufacturerSouriauCategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypeReceptacle, Male PinsNumber of Positions128Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpFastening TypeThreadedPareladedEnvironment ResistantShell Material, FinishGoldContact FinishGoldFeatures-Voltage - Rated-Voltage - Rated-		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypeReceptacle, Male PinsConnector Type128Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangePerminationCrimpFastening TypeThreadedDrientationAShell Material, FinishComposite, Olive Drab Cadmium PlatedShell Material, FinishGoldContact Finish-Features-Voltage - Rated-Current Rating5A	Manufacturer Part Number	D38999/20JJ35HA
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypeReceptacle, Male PinsNumber of Positions128Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpFastening TypeThreadedOrientationEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact Finish-Features-Voltage - Rated-Current Rating5A	Manufacturer	Souriau
Package-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypeReceptacle, Male PinsNumber of Positions128Shell Size - InsertS-35Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpPastening TypeThreadedDrientationEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedShell Material, FinishGoldContact Finish-Contact FinishSoldFeaturesSoldKottage - Rated-Current RatingSA	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypeReceptacle, Male PinsNumber of Positions128Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpFastening TypeThreadedOrientationEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions128Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpFastening TypeAOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishGoldContact Finish-Voltage - Rated-Current Rating5A	Package	-
Number of Positions128Number of Positions25-35Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangeForminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact Finish-Features-Voltage - Rated-Current Rating5A	Series	Military, MIL-DTL-38999 Series III
Shell Size - Insert25-35Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current RatingSA	Connector Type	Receptacle, Male Pins
Shell Size, MILJMounting TypePanel Mount, FlangeFerminationCrimpFastening TypeThreadedOrientationAOrientationEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current RatingSh	Number of Positions	128
Mounting TypePanel Mount, FlangeFerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Shell Size - Insert	25-35
TerminationCrimpFastening TypeThreadedPrientationAIngress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current RatingSA	Shell Size, MIL	J
Fastening TypeThreadedDrientationAIngress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current RatingSA	Mounting Type	Panel Mount, Flange
DrientationAIngress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Termination	Crimp
Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current RatingSA	Fastening Type	Threaded
Shell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Orientation	A
Contact Finish Gold Features - Voltage - Rated - Current Rating 5A	Ingress Protection	Environment Resistant
Features-Voltage - Rated-Current Rating5A	Shell Material, Finish	Composite, Olive Drab Cadmium Plated
Voltage - Rated-Current Rating5A	Contact Finish	Gold
Current Rating 5A	Features	-
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

D38999/20JJ35HA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/20JJ35HA Payment Methods



D38999/20JJ35HA Shipping Methods



If you have any question about D38999/20JJ35HA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com