



### D38999/20WH53JB Information

Heisener.com

Part Number D38999/20WH53JB

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 53POS FLANGE W/SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# D38999/20WH53JB Specifications

Manufacturer Part Number     D38999/20WH53JB       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series III, DTS       Connector Type     Receptacle, Female Sockets       Number of Positions     53       Shell Size - Insert     23-53       Shell Size, MIL     H       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Threaded       Orientation     B       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer Part Number	D38999/20WH53JB
Circular Connectors  Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation B Ingress Protection B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL H Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MILHMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Number of Positions	53
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Size - Insert	23-53
Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	Н
Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  - Current Rating  7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Orientation	В
Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

#### D38999/20WH53JB Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## D38999/20WH53JB Payment Methods



















## D38999/20WH53JB Shipping Methods













If you have any question about D38999/20WH53JB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com