



D38999/20WJ4JD Information

Heisener.com

Part Number D38999/20WJ4JD

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 56POS FLANGE W/SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/20WJ4JD Specifications

Manufacturer Part NumberD38999/20WJ4JDManufacturerTE Connectivity Deutsch ConnectorsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions56Shell Size - Insert25-4Shell Size, MILJMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13AReport errors?		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL J Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Manufacturer Part Number	D38999/20WJ4JD
Circular Connectors Package Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL J Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL J Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL J Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions56Shell Size - Insert25-4Shell Size, MILJMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Package	-
Number of Positions56Shell Size - Insert25-4Shell Size, MILJMounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Number of Positions	56
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Size - Insert	25-4
Termination Crimp Fastening Type Threaded Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Shell Size, MIL	J
Fastening Type Orientation D Ingress Protection Shell Material, Finish Contact Finish Features Shielded Voltage - Rated Current Rating Threaded Threaded D Environment Resistant Aluminum, Olive Drab Cadmium Plated Gold Food Food Threaded Threaded	Mounting Type	Panel Mount, Flange
Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold	Orientation	D
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	7.5A, 13A
		Report errors?

D38999/20WJ4JD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/20WJ4JD Payment Methods



















D38999/20WJ4JD Shipping Methods













If you have any question about D38999/20WJ4JD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com