



D38999/24FE99HN Information

Heisener.com

Part Number D38999/24FE99HN

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 23POS JAM NUT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24FE99HN Specifications

Manufacturer Part Number D38999/24FE99HN Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 17-99 Shell Size, MIL E Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions23Shell Size - Insert17-99Shell Size, MILEMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Manufacturer Part Number	D38999/24FE99HN
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions23Shell Size - Insert17-99Shell Size, MILEMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 17-99 Shell Size, MIL E Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions23Shell Size - Insert17-99Shell Size, MILEMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions23Shell Size - Insert17-99Shell Size, MILEMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Package	-
Number of Positions23Shell Size - Insert17-99Shell Size, MILEMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Number of Positions	23
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Shell Size - Insert	17-99
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Size, MIL	E
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Nickel Plated
Voltage - Rated - Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A, 13A
		Report errors?

D38999/24FE99HN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24FE99HN Payment Methods



















D38999/24FE99HN Shipping Methods













If you have any question about D38999/24FE99HN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com