



### D38999/24FF32SA Information

Heisener.com

Part Number D38999/24FF32SA

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 32POS JAM NUT W/SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## D38999/24FF32SA Specifications

Manufacturer Part Number     D38999/24FF32SA       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     Military, MIL-DTL-38999 Series III, DTS       Connector Type     Receptacle, Female Sockets       Number of Positions     32       Shell Size - Insert     19-32       Shell Size, MIL     F       Mounting Type     Panel Mount, Bulkhead - Front Side Nut       Termination     Crimp       Fastening Type     Threaded       Orientation     A       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     7.5A		
Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series III, DTS         Connector Type       Receptacle, Female Sockets         Number of Positions       32         Shell Size - Insert       19-32         Shell Size, MIL       F         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Crimp         Fastening Type       Threaded         Orientation       A         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated         Contact Finish       Gold         Features       Shielded         Voltage - Rated       -         Current Rating       7.5A	Manufacturer Part Number	D38999/24FF32SA
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions32Shell Size - Insert19-32Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 32 Shell Size - Insert 19-32 Shell Size, MIL F Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 32 Shell Size - Insert 19-32 Shell Size, MIL F Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions32Shell Size - Insert19-32Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions32Shell Size - Insert19-32Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert  Shell Size, MIL  F  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Crimp  Fastening Type  Threaded  Orientation  A  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  -  Current Rating  7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Crimp  Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded  Voltage - Rated Current Rating 7.5A	Number of Positions	32
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Threaded  Orientation A  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated  Contact Finish Gold  Features Shielded  Voltage - Rated -  Current Rating 7.5A	Shell Size - Insert	19-32
Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	F
Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Orientation	A
Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Nickel Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

### D38999/24FF32SA Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## D38999/24FF32SA Payment Methods



















# D38999/24FF32SA Shipping Methods













If you have any question about D38999/24FF32SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com