



### D38999/24FG35HA Information

Heisener.com

Part Number D38999/24FG35HA

Manufacturer TE Connectivity Deutsch Connectors

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 79POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## D38999/24FG35HA Specifications

Manufacturer Part Number     D38999/24FG35HA       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     Military, MIL-DTL-38999 Series III, DTS       Connector Type     Receptacle, Male Pins       Number of Positions     79       Shell Size - Insert     21-35       Shell Size, MIL     G       Mounting Type     Panel Mount, Bulkhead - Front Side Nut       Termination     Crimp       Fastening Type     Threaded       Orientation     A       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series III, DTS  Connector Type Receptacle, Male Pins  Number of Positions 79 Shell Size - Insert 21-35 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Manufacturer Part Number	D38999/24FG35HA
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions79Shell Size - Insert21-35Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 79 Shell Size - Insert 21-35 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions79Shell Size - Insert21-35Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions79Shell Size - Insert21-35Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Package	-
Number of Positions79Shell Size - Insert21-35Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Connector Type	Receptacle, Male Pins
Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Number of Positions	79
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Shell Size - Insert	21-35
Termination Crimp Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Shell Size, MIL	G
Fastening Type Threaded Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Orientation	A
Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated - Current Rating 5A	Shell Material, Finish	Aluminum, Nickel Plated
Voltage - Rated - Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

### D38999/24FG35HA Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### D38999/24FG35HA Payment Methods



















# D38999/24FG35HA Shipping Methods













If you have any question about D38999/24FG35HA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com