



# D38999/24FG39SN Information

Heisener.com

Part Number D38999/24FG39SN

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN RCPT 39POS JAM NUT W/SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## D38999/24FG39SN Specifications

Manufacturer Part Number     D38999/24FG39SN       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series III, DTS       Connector Type     Receptacle, Female Sockets       Number of Positions     39       Shell Size - Insert     21-39       Shell Size, MIL     G       Mounting Type     Panel Mount, Bulkhead - Front Side Nut       Termination     Crimp       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     7.5A, 13A   Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert21-39Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Manufacturer Part Number	D38999/24FG39SN
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert21-39Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 21-39 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert21-39Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert21-39Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Package	-
Number of Positions39Shell Size - Insert21-39Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated  Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 7.5A, 13A	Number of Positions	39
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Shell Size - Insert	21-39
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Size, MIL	G
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated - Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Nickel Plated
Voltage - Rated - Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A, 13A
		Report errors?

#### D38999/24FG39SN Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### D38999/24FG39SN Payment Methods



















# D38999/24FG39SN Shipping Methods













If you have any question about D38999/24FG39SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com