



D38999/24FJ43SB Information

Heisener.com

Part Number D38999/24FJ43SB

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 43POS JAM NUT W/SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24FJ43SB Specifications

Manufacturer Part Number D38999/24FJ43SB Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 43 Shell Size - Insert 25-43 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 43 Shell Size - Insert 25-43 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation B Ingress Protection Benvironment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Manufacturer Part Number	D38999/24FJ43SB
Circular Connectors Package Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 43 Shell Size - Insert 25-43 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 43 Shell Size - Insert 25-43 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 43 Shell Size - Insert 25-43 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions43Shell Size - Insert25-43Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Package	-
Number of Positions Shell Size - Insert 25-43 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Number of Positions	43
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Size - Insert	25-43
Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Shell Size, MIL	J
Fastening Type Orientation B Ingress Protection Environment Resistant Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Orientation	В
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Nickel Plated
Voltage - Rated - Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Shielded
	Voltage - Rated	-
Donout among 9	Current Rating	7.5A, 13A
Report errors?		Report errors?

D38999/24FJ43SB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24FJ43SB Payment Methods



















D38999/24FJ43SB Shipping Methods













If you have any question about D38999/24FJ43SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com