



D38999/24FJ61PC Information

Heisener.com

Part Number D38999/24FJ61PC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 61POS JAM NUT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24FJ61PC Specifications

| Manufacturer Part Number D38999/24FJ6IPC Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 25-61 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - Report errors? | | |
|---|--------------------------|---|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 25-61 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | Manufacturer Part Number | D38999/24FJ61PC |
| Circular Connectors Package Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 25-61 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | Manufacturer | Amphenol Aerospace Operations |
| Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 25-61 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 25-61 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | | Circular Connectors |
| Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 25-61 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Package | - |
| Number of Positions Shell Size - Insert 25-61 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | Series | Military, MIL-DTL-38999 Series III, Tri-Start? TV |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | Number of Positions | 61 |
| Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Shell Size - Insert | 25-61 |
| Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Shell Size, MIL | J |
| Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | Orientation | C |
| Contact Finish Gold Features Shielded Voltage - Rated - Current Rating - | Ingress Protection | Environment Resistant |
| Features Shielded Voltage - Rated - Current Rating - | Shell Material, Finish | Aluminum, Nickel Plated, Electroless |
| Voltage - Rated - Current Rating - | Contact Finish | Gold |
| Current Rating - | Features | Shielded |
| - | Voltage - Rated | - |
| Report errors? | Current Rating | - |
| | | Report errors? |

D38999/24FJ61PC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24FJ61PC Payment Methods



















D38999/24FJ61PC Shipping Methods













If you have any question about D38999/24FJ61PC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com