

Heisener.com

D38999/24KJ29SN-UCSB4

D38999/24KJ29SN-UCSB4 Information

Part Number D38999/24KJ29SN-UCSB4
Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT FMALE 29POS GOLD CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24KJ29SN-UCSB4 Specifications

| Manufacturer Part NumberD38999/24KJ29SN-UCSB4ManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypeReceptacle, Female SocketsNumber of Positions29Shell Size - Insert25-29Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating-Report errors? | | |
|---|--------------------------|---|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Female Sockets Number of Positions 29 Shell Size - Insert 25-29 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated Current Rating - | Manufacturer Part Number | D38999/24KJ29SN-UCSB4 |
| Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV Connector Type Receptacle, Female Sockets Number of Positions 29 Shell Size - Insert 25-29 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated Current Rating - | Manufacturer | Amphenol Aerospace Operations |
| Package-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypeReceptacle, Female SocketsNumber of Positions29Shell Size - Insert25-29Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | Category | Connectors, Interconnects |
| SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypeReceptacle, Female SocketsNumber of Positions29Shell Size - Insert25-29Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions29Shell Size - Insert25-29Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | Package | - |
| Number of Positions29Shell Size - Insert25-29Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | Series | Military, MIL-DTL-38999 Series III, Tri-Start? TV |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated Current Rating - | Connector Type | Receptacle, Female Sockets |
| Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | Number of Positions | 29 |
| Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | Shell Size - Insert | 25-29 |
| Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated - Current Rating - | Shell Size, MIL | J |
| Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated - Current Rating - | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated - Current Rating - | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Stainless Steel Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated - Current Rating - | Fastening Type | Threaded |
| Shell Material, FinishStainless SteelContact FinishGoldFeaturesFirewall Usage, Shrink BootVoltage - Rated-Current Rating- | Orientation | N (Normal) |
| Contact Finish Gold Features Firewall Usage, Shrink Boot Voltage - Rated - Current Rating - | Ingress Protection | Environment Resistant |
| Features Firewall Usage, Shrink Boot Voltage - Rated - Current Rating - | Shell Material, Finish | Stainless Steel |
| Voltage - Rated - Current Rating - | Contact Finish | Gold |
| Current Rating - | Features | Firewall Usage, Shrink Boot |
| - | Voltage - Rated | - |
| Report errors? | Current Rating | - |
| | | Report errors? |

D38999/24KJ29SN-UCSB4 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24KJ29SN-UCSB4 Payment Methods



















D38999/24KJ29SN-UCSB4 Shipping Methods













If you have any question about D38999/24KJ29SN-UCSB4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com