



D38999/24MH55SN Information

Heisener.com

Part Number D38999/24MH55SN

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 55POS JAM NUT W/SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24MH55SN Specifications

Manufacturer Part Number D38999/24MH55SN Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series III, ACT Connector Type Receptacle, Female Sockets Number of Positions 55 Shell Size - Insert 23-55 Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypeReceptacle, Female SocketsNumber of Positions55Shell Size - Insert23-55Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer Part Number	D38999/24MH55SN
Package - Series Military, MIL-DTL-38999 Series III, ACT Connector Type Receptacle, Female Sockets Number of Positions 55 Shell Size - Insert 23-55 Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7,5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, ACT Connector Type Receptacle, Female Sockets Number of Positions 55 Shell Size - Insert 23-55 Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, ACT Connector Type Receptacle, Female Sockets Number of Positions 55 Shell Size - Insert 23-55 Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions55Shell Size - Insert23-55Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions55Shell Size - Insert23-55Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-38999 Series III, ACT
Shell Size - Insert Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Features Shielded Voltage - Rated Current Rating THE Panel Mount, Bulkhead - Front Side Nut Crimp Contact Finith Gold Features Shielded 7.5A	Number of Positions	55
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Size - Insert	23-55
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	Н
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Composite, Nickel Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

D38999/24MH55SN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24MH55SN Payment Methods



















D38999/24MH55SN Shipping Methods













If you have any question about D38999/24MH55SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com