



D38999/24WB98PB Information

Heisener.com

Part Number D38999/24WB98PB

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 6POS JAM NUT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24WB98PB Specifications

Manufacturer Part Number D38999/24WB98PB Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 11-98 Shell Size, MIL B Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer Part Number	D38999/24WB98PB
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 11-98 Shell Size, MIL B Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 11-98 Shell Size, MIL B Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions Shell Size - Insert 11-98 Shell Size, MIL B Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL B Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A	Number of Positions	6
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Size - Insert	11-98
Termination Crimp Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	В
Fastening Type Threaded Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Orientation	В
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

D38999/24WB98PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24WB98PB Payment Methods



















D38999/24WB98PB Shipping Methods













If you have any question about D38999/24WB98PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com