

Heisener.com

## D38999/24WE6SN-URSB3

### D38999/24WE6SN-URSB3 Information

Part Number D38999/24WE6SN-URSB3
Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects
Circular Connectors

**Description** CONN RCPT FMALE 6POS GOLD CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# D38999/24WE6SN-URSB3 Specifications

Manufacturer Part Number     D38999/24WE6SN-URSB3       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series III, Tri-Start? TV       Connector Type     Receptacle, Female Sockets       Number of Positions     6       Shell Size - Insert     17-6       Shell Size, MIL     E       Mounting Type     Panel Mount, Bulkhead, Right Angle       Termination     Crimp       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     Shrink Boot       Voltage - Rated     -       Current Rating     -       Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV  Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL E Mounting Type Panel Mount, Bulkhead, Right Angle  Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold Features Voltage - Rated Current Rating - Current Rating -	Manufacturer Part Number	D38999/24WE6SN-URSB3
Circular Connectors  Package - Series Military, MIL-DTL-38999 Series III, Tri-Start? TV  Connector Type Receptacle, Female Sockets  Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL E Mounting Type Panel Mount, Bulkhead, Right Angle  Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold Features Shrink Boot  Voltage - Rated Current Rating -	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert17-6Shell Size, MILEMounting TypePanel Mount, Bulkhead, Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink BootVoltage - Rated-Current Rating-	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert17-6Shell Size, MILEMounting TypePanel Mount, Bulkhead, Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink BootVoltage - Rated-Current Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert17-6Shell Size, MILEMounting TypePanel Mount, Bulkhead, Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink BootVoltage - Rated-Current Rating-	Package	-
Number of Positions6Shell Size - Insert17-6Shell Size, MILEMounting TypePanel Mount, Bulkhead, Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink BootVoltage - Rated-Current Rating-	Series	Military, MIL-DTL-38999 Series III, Tri-Start? TV
Shell Size - Insert  Shell Size, MIL  E  Mounting Type  Panel Mount, Bulkhead, Right Angle  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Shrink Boot  Voltage - Rated  -  Current Rating  -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead, Right Angle  Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Shrink Boot  Voltage - Rated - Current Rating -	Number of Positions	6
Mounting Type Panel Mount, Bulkhead, Right Angle Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Voltage - Rated - Current Rating -	Shell Size - Insert	17-6
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Voltage - Rated - Current Rating -	Shell Size, MIL	E
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Voltage - Rated - Current Rating -	Mounting Type	Panel Mount, Bulkhead, Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Voltage - Rated - Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Voltage - Rated - Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Gold  Features  Shrink Boot  Voltage - Rated  Current Rating  -	Orientation	N (Normal)
Contact Finish Gold Features Shrink Boot Voltage - Rated - Current Rating -	Ingress Protection	Environment Resistant
Features Shrink Boot  Voltage - Rated - Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shrink Boot
-	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

### D38999/24WE6SN-URSB3 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### D38999/24WE6SN-URSB3 Payment Methods



















## D38999/24WE6SN-URSB3 Shipping Methods













If you have any question about D38999/24WE6SN-URSB3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com