



D38999/24WF35HE Information

Heisener.com

Part Number D38999/24WF35HE

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 66POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24WF35HE Specifications

Manufacturer Part Number D38999/24WF35HE Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 66 Shell Size - Insert 19-35 Shell Size, MIL F Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions66Shell Size - Insert19-35Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Manufacturer Part Number	D38999/24WF35HE
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions66Shell Size - Insert19-35Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 66 Shell Size - Insert 19-35 Shell Size, MIL F Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 66 Shell Size - Insert 19-35 Shell Size, MIL F Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions66Shell Size - Insert19-35Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Package	-
Number of Positions66Shell Size - Insert19-35Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL F Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Connector Type	Receptacle, Male Pins
Shell Size, MILFMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A	Number of Positions	66
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Shell Size - Insert	19-35
Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Shell Size, MIL	F
Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Orientation	E
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

D38999/24WF35HE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24WF35HE Payment Methods



















D38999/24WF35HE Shipping Methods













If you have any question about D38999/24WF35HE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com