



D38999/24WG41PC Information

Heisener.com

Part Number D38999/24WG41PC

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 41POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24WG41PC Specifications

Manufacturer Part Number D38999/24WG41PC Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 41 Shell Size - Insert 21-41 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 41 Shell Size - Insert Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation C Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Manufacturer Part Number	D38999/24WG41PC
Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 41 Shell Size - Insert 21-41 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 41 Shell Size - Insert 21-41 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 41 Shell Size - Insert 21-41 Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions41Shell Size - Insert21-41Shell Size, MILGMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions Shell Size - Insert 21-41 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL G Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Number of Positions	41
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Size - Insert	21-41
Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	G
Fastening Type Threaded Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Cold Shielded - Current Rating	Orientation	C
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

D38999/24WG41PC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24WG41PC Payment Methods



















D38999/24WG41PC Shipping Methods













If you have any question about D38999/24WG41PC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com