



D38999/24WH53SE Information

Heisener.com

Part Number D38999/24WH53SE

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 53POS JAM NUT W/SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/24WH53SE Specifications

Manufacturer Part Number D38999/24WH53SE Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer Part Number	D38999/24WH53SE
Package-SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Female Sockets Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Female SocketsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions53Shell Size - Insert23-53Shell Size, MILHMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL H Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated - Current Rating 7.5A	Number of Positions	53
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Size - Insert	23-53
Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	Н
Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold	Orientation	E
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

D38999/24WH53SE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/24WH53SE Payment Methods

































If you have any question about D38999/24WH53SE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com