



## D38999/24WJ20PE Information

Heisener.com

Part Number D38999/24WJ20PE

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 30POS JAM NUT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# D38999/24WJ20PE Specifications

Series Military, MIL-DTL-38999 Series III, DTS  Connector Type Receptacle, Male Pins  Number of Positions 30  Shell Size - Insert 25-20  Shell Size, MIL J  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp		
Category Circular Connectors Circular Connectors  Package - Series Military, MIL-DTL-38999 Series III, DTS  Connector Type Receptacle, Male Pins  Number of Positions 30 Shell Size - Insert 25-20 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Manufacturer Part Number	D38999/24WJ20PE
Circular Connectors  Package Series Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 30 Shell Size - Insert 25-20 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated - Current Rating 7,5A, 13A, 23A, 46A	Manufacturer	TE Connectivity Deutsch Connectors
Package - Military, MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 30 Shell Size - Insert 25-20 Shell Size, MIL J Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A, 23A, 46A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, DTS  Connector Type Receptacle, Male Pins  Number of Positions 30  Shell Size - Insert 25-20  Shell Size, MIL J  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Threaded  Orientation E  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features Shielded  Voltage - Rated  Current Rating 7.5A, 13A, 23A, 46A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions30Shell Size - Insert25-20Shell Size, MILJMounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A, 23A, 46A	Package	-
Number of Positions  Shell Size - Insert  25-20  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Crimp  Fastening Type  Threaded  Orientation  E  Ingress Protection  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Features  Shielded  Voltage - Rated  Current Rating  7.5A, 13A, 23A, 46A	Series	Military, MIL-DTL-38999 Series III, DTS
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Crimp  Fastening Type  Threaded  Orientation  E  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Features  Shielded  Voltage - Rated  Current Rating  7.5A, 13A, 23A, 46A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Shielded  Voltage - Rated Current Rating 7.5A, 13A, 23A, 46A	Number of Positions	30
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Threaded  Orientation E  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features Shielded  Voltage - Rated  Current Rating 7.5A, 13A, 23A, 46A	Shell Size - Insert	25-20
Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A, 23A, 46A	Shell Size, MIL	J
Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  Cold  Shielded  - Current Rating	Orientation	E
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A, 13A, 23A, 46A	Contact Finish	Gold
Current Rating 7.5A, 13A, 23A, 46A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	7.5A, 13A, 23A, 46A
		Report errors?

### D38999/24WJ20PE Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## D38999/24WJ20PE Payment Methods



















## D38999/24WJ20PE Shipping Methods













If you have any question about D38999/24WJ20PE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com