

D38999/26FB35SN-UW

D38999/26FB35SN-UW Information

G	Heisener.com	 D38999/26FB35SN-UW Amphenol Aerospace Operations Connectors, Interconnects Circular Connectors CONN PLUG FMALE 13POS GOLD CRIMP - For the pricing/inventory/lead time, please contact	
For	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D38999/26FB35SN-UW Specifications

ManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-PackageMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedNormaliN(Normal)Ingress ProtectionAuminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishShielding DeviceVoltage - Rated-Current Rating-Current Rating-	Manufacturer Part Number	D38999/26FB35SN-UW
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating-	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions13Shell Size - InsertI1-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeN(Normal)Ingress ProtectionSnivornment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessShell Material, FinishSilding DeviceVoltage - RatedSilding DeviceVoltage - RatedSilding DeviceVoltage - Rated-Corrent Rating-StartedSilding DeviceStarted Rated-Started Rated Rated-Started Rated	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishShielding DeviceVoltage - Rated-Current Rating-Current Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Package	-
Number of Positions13Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Series	Military, MIL-DTL-38999 Series III, Tri-Start? TV
Shell Size - Insert11-35Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShielding DeviceVoltage - Rated-Current Rating-	Connector Type	Plug, Female Sockets
Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-Shell Material, Finish-Shielding Device-Shell Material Finish-Shell Stated-Shell Stated-Shell Stated-Shell Stated-Shell Stated-State Stated-State State-State State State-State State St	Number of Positions	13
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)OrientationEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Shell Size - Insert	11-35
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Shell Size, MIL	В
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Termination	Crimp
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Orientation	N (Normal)
Contact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Ingress Protection	Environment Resistant
FeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating-	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated - Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielding Device
-	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

D38999/26FB35SN-UW Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

D38999/26FB35SN-UW Payment Methods



D38999/26FB35SN-UW Shipping Methods



If you have any question about D38999/26FB35SN-UW, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com