

D38999/26FC98PN

D38999/26FC98PN Information



rt Number	D38999/26FC98PN	
anufacturer	ITT Cannon, LLC	
tegory	Connectors, Interconnects Circular Connectors	
scription	CONN PLUG 10POS INLINE W/PINS	
ckage	-	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D38999/26FC98PN Specifications

Manufacturer Part NumberD38999/26FC98PNManufacturerITC Cannon, LLCCategoryConnectors, InterconnectsPackage-PackageMiltary, MIL-DTL-3899 Series III, KJASeriesMiltary, MIL-DTL-3899 Series III, KJAConnector TypePlog, Male PinsNumber of Positions0Shell Size - Insert3-98Shell Size, MILCMouning TypeFree Hanging (In-Line)TerminationCrimpFastening TypeNormal,Normal, FinishAluminum Alloy, Nickel Plated, ElectrolessShell Material, FinishGoldForturesSheldedYoltage PackadedSheldedYoltage PackadedSheldedYoltage RatedSheldedYoltage Yoltage YoltageSheldedYolt		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, KJAConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert13-98Shell Size, MILCMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionAuminum Alloy, Nickel Plated, ElectrolessShell Material, FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-Current Rating-	Manufacturer Part Number	D38999/26FC98PN
Indext of the section of the sectio	Manufacturer	ITT Cannon, LLC
Package.SeriesMilitary, MIL-DTL-38999 Series III, KJAConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert13-98Shell Size, MILCMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesSheldedVoltage - RatedSheldedCortent RatingSheldedCortent RatingSheldedShell RatedSheldedStell RatedSheldedSte	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, KJAConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert13-98Shell Size, MILCMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishSieldedVoltage - RatedSieldedVoltage - Rated.Current Rating.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.Statemage.		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions10Shumber of Positions13-98Shell Size - InsertCMounting TypeFree Hanging (In-Line)Mounting TypeCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFoaturesShieldedVoltage - RatedSnieldedCurrent Rating-Current Rating-	Package	-
Number of PositionsI0Shell Size - Insert13-98Shell Size, MILCMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShieldedVoltage - Rated-Current Rating-	Series	Military, MIL-DTL-38999 Series III, KJA
Shell Size - Insert13-98Shell Size, MILCMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-Shell MaterialShielded	Connector Type	Plug, Male Pins
Shell Size, MILCMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishSideddYoltage - Rated.Yoltage - Rateng.Current Rating.	Number of Positions	10
Mounting TypeFree Hanging (In-Line)FreminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-Current Rating-	Shell Size - Insert	13-98
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-	Shell Size, MIL	С
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-	Termination	Crimp
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-	Orientation	N (Normal)
Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating-	Ingress Protection	Environment Resistant
FeaturesShieldedVoltage - Rated-Current Rating-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output-Output- <t< td=""><td>Shell Material, Finish</td><td>Aluminum Alloy, Nickel Plated, Electroless</td></t<>	Shell Material, Finish	Aluminum Alloy, Nickel Plated, Electroless
Voltage - Rated-Current Rating-	Contact Finish	Gold
Current Rating -	Features	Shielded
-	Voltage - Rated	-
	Current Rating	-
Report errors'		Report errors?

D38999/26FC98PN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/26FC98PN Payment Methods





If you have any question about D38999/26FC98PN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com