

D38999/26JB98SN

D38999/26JB98SN Information

Heisener.com Order service can's terr	Part Number Manufacturer Category Description Package	D38999/26JB98SN Souriau Connectors, Interconnects Circular Connectors CONN PLUG 6POS STRAIGHT W/SCKT - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D38999/26JB98SN Specifications

ManufacturerSouriauCategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionGoldShell Material, FinishGoldVoltage - RatedShieldedVoltage - RatedShieldedVoltage - RatedShieldedContact FinishShieldedContact FinishShieldedContact FinishShieldedContact Fastening SeriesShieldedFeaturesShieldedContact FinishShieldedShieldedShielded		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShelledFeaturesShieldedVoltage - Rated-Current Rating7,5A	Manufacturer Part Number	D38999/26JB98SN
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShieldedVoltage - Rated-Current Rating7.5A	Manufacturer	Souriau
Package-SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShelledaVoltage - RatedShelledaVoltage - RatedShelledaCurrent RatingShelledaCurrent RatingShelledaCurrent RatingShelledaCurrent RatingShelledaCurrent RatingShelledaCurrent RatingShelledaShell StendeShelledaShell StendeShelledaShell StendeShelledaShell StendeShelledaShell StendeShelledaShell StendeShell StendeStendeShell StendeStendeShell StendeStendeStendeStendeStendeStendeStendeStendeStendeStendeStendeStendeStendeStendeStendeStende </td <td>Category</td> <td>Connectors, Interconnects</td>	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series IIIConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedFeaturesShieldedVoltage - Rated-Current Rating7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions6Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedFoaturesShieldedVoltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-38999 Series III
Shell Size - Insert11-98Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedFoaturesShieldedVoltage - Rated-Current Rating7.5A	Connector Type	Plug, Female Sockets
Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Corrent Rating7.5A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Size - Insert	11-98
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Size, MIL	В
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Termination	Crimp
Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Fastening Type	Threaded
Shell Material, FinishComposite, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Orientation	N (Normal)
Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Ingress Protection	Environment Resistant
FeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Material, Finish	Composite, Olive Drab Cadmium Plated
Voltage - Rated-Current Rating7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

D38999/26JB98SN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/26JB98SN Payment Methods





If you have any question about D38999/26JB98SN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com