



D38999/26MA35PN Information

www.tersener.com

For Reference Only

Part Number D38999/26MA35PN

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG MALE 6POS GOLD CRIMP

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D38999/26MA35PN Specifications

Manufacturer Part Number D38999/26MA35PN Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series III, ACT Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 9-35 Shell Size, MIL A Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert9-35Shell Size, MILAMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel Plated, ElectrolessContact FinishGoldFeaturesCoupling NutVoltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer Part Number	D38999/26MA35PN
Circular Connectors Package - Series Military, MIL-DTL-38999 Series III, ACT Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 9-35 Shell Size, MIL A Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Couling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Manufacturer	TE Connectivity Deutsch Connectors
Package-SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert9-35Shell Size, MILAMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel Plated, ElectrolessContact FinishGoldFeaturesCoupling NutVoltage - Rated400VAC, 550VDCCurrent Rating-	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series III, ACT Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 9-35 Shell Size, MIL A Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert9-35Shell Size, MILAMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel Plated, ElectrolessContact FinishGoldFeaturesCoupling NutVoltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions6Shell Size - Insert9-35Shell Size, MILAMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel Plated, ElectrolessContact FinishGoldFeaturesCoupling NutVoltage - Rated400VAC, 550VDCCurrent Rating-	Series	Military, MIL-DTL-38999 Series III, ACT
Shell Size - Insert Shell Size, MIL A Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating A A A A A A A Bena Crimp Crimp Crimp Composite Composite Composite Coupling Nut C	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel Plated, ElectrolessContact FinishGoldFeaturesCoupling NutVoltage - Rated400VAC, 550VDCCurrent Rating-	Shell Size - Insert	9-35
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	A
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Composite, Nickel Plated, Electroless Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Orientation	N (Normal)
Contact Finish Gold Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features Coupling Nut Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Composite, Nickel Plated, Electroless
Voltage - Rated 400VAC, 550VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Coupling Nut
	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
		Report errors?

D38999/26MA35PN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/26MA35PN Payment Methods



















D38999/26MA35PN Shipping Methods













If you have any question about D38999/26MA35PN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com