



### D38999/26MJ24HN Information

Heisener.com

Part Number D38999/26MJ24HN

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 24POS STRGHT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# D38999/26MJ24HN Specifications

| Manufacturer Part Number     D38999/26MJ24HN       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series III, ACT       Connector Type     Plug, Male Pins       Number of Positions     24       Shell Size - Insert     25-24       Shell Size, MIL     J       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Composite, Nickel Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     13A, 23A |                          |   |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypePlug, Male PinsNumber of Positions24Shell Size - Insert25-24Shell Size, MILJMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A   | Manufacturer Part Number | D38999/26MJ24HN                         |
| Package-SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypePlug, Male PinsNumber of Positions24Shell Size - Insert25-24Shell Size, MILJMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A  | Manufacturer             | TE Connectivity Deutsch Connectors      |
| Package-SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypePlug, Male PinsNumber of Positions24Shell Size - Insert25-24Shell Size, MILJMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A  | Category                 | Connectors, Interconnects               |
| SeriesMilitary, MIL-DTL-38999 Series III, ACTConnector TypePlug, Male PinsNumber of Positions24Shell Size - Insert25-24Shell Size, MILJMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A  |                          | Circular Connectors                     |
| Connector TypePlug, Male PinsNumber of Positions24Shell Size - Insert25-24Shell Size, MILJMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A   | Package                  | -                                       |
| Number of Positions24Shell Size - Insert25-24Shell Size, MILJMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A  | Series                   | Military, MIL-DTL-38999 Series III, ACT |
| Shell Size - Insert Shell Size, MIL J Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 13A, 23A  | Connector Type           | Plug, Male Pins                         |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated  Contact Finish Features Shielded  Voltage - Rated Current Rating  Is a Single Hanging (In-Line)  Crimp Free Hanging (In-Line)  Crimp  Crimp  Crimp  Chip  Gold  Features Shielded  - Current Rating  Is a A, 23A  | Number of Positions      | 24                                      |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishComposite, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A, 23A   | Shell Size - Insert      | 25-24                                   |
| Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 13A, 23A   | Shell Size, MIL          | J                                       |
| Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Composite, Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  -  Current Rating  13A, 23A  | Mounting Type            | Free Hanging (In-Line)                  |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 13A, 23A   | Termination              | Crimp                                   |
| Ingress Protection Environment Resistant Shell Material, Finish Composite, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 13A, 23A  | Fastening Type           | Threaded                                |
| Shell Material, Finish  Composite, Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  - Current Rating  13A, 23A   | Orientation              | N (Normal)                              |
| Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 13A, 23A   | Ingress Protection       | Environment Resistant                   |
| Features Shielded  Voltage - Rated - Current Rating 13A, 23A  | Shell Material, Finish   | Composite, Nickel Plated                |
| Voltage - Rated - Current Rating 13A, 23A   | Contact Finish           | Gold                                    |
| Current Rating 13A, 23A   | Features                 | Shielded                                |
| •   | Voltage - Rated          | -                                       |
| Report errors?  | Current Rating           | 13A, 23A                                |
| K.  |                          | Report errors?                          |

#### D38999/26MJ24HN Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### D38999/26MJ24HN Payment Methods





















# D38999/26MJ24HN Shipping Methods













If you have any question about D38999/26MJ24HN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com