

D38999/26WB2SN-UW

D38999/26WB2SN-UW Information

Heisener.com	 D38999/26WB2SN-UW Amphenol Aerospace Operations Connectors, Interconnects Circular Connectors CONN PLUG FMALE 2POS GOLD CRIMP - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D38999/26WB2SN-UW Specifications

ManufacturerAmphenol Aerospace OperationsCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishShielding DeviceYotage - Rated-Current Rating-Current Rating </th <th></th> <th></th>		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishShielding DeviceVoltage - Rated-Current Rating-Current Rating-	Manufacturer Part Number	D38999/26WB2SN-UW
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishShielding DeviceVoltage - Rated-Current Rating-Current Rating-	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedFeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating-Current Rating-Current Rating-Current Rating-Start Series-Start Series-<	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedFeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Package	-
Number of Positions2Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Series	Military, MIL-DTL-38999 Series III, Tri-Start? TV
Shell Size - Insert11-2Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShielding DeviceVoltage - Rated-Current Rating-Shell Material, FinishShielding Device	Connector Type	Plug, Female Sockets
Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSileiding DeviceFeaturesSileiding DeviceVoltage - Rated-Current Rating-Shell Material, Finish-Shell Material, FinishSileiding DeviceFeaturesSileiding DeviceSoltage - Rated-Surent Rating-Soltage - Rated-Surent Rating-Soltage - Rated-Soltage - Rated- <td>Number of Positions</td> <td>2</td>	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)OrientationEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Shell Size - Insert	11-2
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Shell Size, MIL	В
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Termination	Crimp
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Orientation	N (Normal)
Contact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-	Ingress Protection	Environment Resistant
FeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating-	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielding Device
-	Voltage - Rated	-
Report errors?	Current Rating	-
Report chois.		Report errors?

D38999/26WB2SN-UW Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/26WB2SN-UW Payment Methods





If you have any question about D38999/26WB2SN-UW, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com