

D38999/26WB5SN-US

D38999/26WB5SN-US Information

| Heisener.com | D38999/26WB5SN-US Amphenol Aerospace Operations Connectors, Interconnects Circular Connectors CONN PLUG FMALE 5POS GOLD CRIMP - For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D38999/26WB5SN-US Specifications

| ManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-PackageMilitary, MIL-DTL-38999 Series III, Tri-Start? TVPonector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedNiroment ResistantN(Normal)Ingress ProtectionGoldShell Material, FinishGoldFeaturesShielding DeviceYoltage - Rated- | | |
|--|--------------------------|---|
| CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishShielding DeviceVoltage - Rated-Current Rating-Current Rating- | Manufacturer Part Number | D38999/26WB5SN-US |
| Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldVoltage - Rated-Voltage - Rated-Current Rating-Current Rating- | Manufacturer | Amphenol Aerospace Operations |
| Package-SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeN(Normal)Ingress ProtectionSnivonment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSnielding DeviceVoltage - RatedSnielding DeviceVoltage - Rated-Current Rating-Statening Type- | Category | Connectors, Interconnects |
| SeriesMilitary, MIL-DTL-38999 Series III, Tri-Start? TVConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating- | | Circular Connectors |
| Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Package | - |
| Number of Positions5Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-Current Rating- | Series | Military, MIL-DTL-38999 Series III, Tri-Start? TV |
| Shell Size - Insert11-5Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShielding DeviceVoltage - Rated-Current Rating-Shell State-Shell State-State-State-State-State-State-State-State-State-State-State-State-State-State-State-State-State-State-State-< | Connector Type | Plug, Female Sockets |
| Shell Size, MILBMounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating-Statemann-Shell Statemann-StatemannStatemann | Number of Positions | 5 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Shell Size - Insert | 11-5 |
| TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Shell Size, MIL | В |
| Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Mounting Type | Free Hanging (In-Line) |
| OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Termination | Crimp |
| Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Fastening Type | Threaded |
| Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Orientation | N (Normal) |
| Contact FinishGoldFeaturesShielding DeviceVoltage - Rated-Current Rating- | Ingress Protection | Environment Resistant |
| FeaturesShielding DeviceVoltage - Rated-Current Rating- | Shell Material, Finish | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated - Current Rating - | Contact Finish | Gold |
| Current Rating - | Features | Shielding Device |
| - | Voltage - Rated | - |
| Report errors? | Current Rating | - |
| | | Report errors? |

D38999/26WB5SN-US Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D38999/26WB5SN-US Payment Methods





If you have any question about D38999/26WB5SN-US, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com