



DA10-050EU Information



For Reference Only

Part Number DA10-050EU

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 10W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DA10-050EU Specifications

| Manufacturer Part Number DA10-050EU Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) Package - Series DA10 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.98" L x 1.56" W x 2.45" H (25.0mm x 39.5mm x 62.3mm) | - | |
|--|---------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series DA10 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Manufacturer Part Number | DA10-050EU |
| Package Series DA10 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output Current - Output (Max) Power (Watts) 10W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Output Connector USB A Receptacle | Manufacturer | Artesyn Embedded Technologies |
| Package - Series DA10 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Category | Power Supplies - External/Internal (Off-Board) |
| SeriesDA10Region UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $2A$ Power (Watts) $10W$ No Load Power Consumption $75mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorUSB A Receptacle | | AC DC Desktop, Wall Adapters |
| Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Package | - |
| Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Series | DA10 |
| Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Region Utilized | Europe |
| Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Form | Wall Mount |
| Voltage - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Input Type | Fixed Blade |
| Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature Output Connector USB A Receptacle | Voltage - Input | 90 ~ 264 VAC |
| Power (Watts) No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Voltage - Output | 5V |
| No Load Power Consumption 75mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorUSB A Receptacle | Current - Output (Max) | 2A |
| Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Power (Watts) | 10W |
| ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorUSB A Receptacle | No Load Power Consumption | 75mW (Max) |
| Efficiency Level VI, CoC Tier 2 Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB A Receptacle | Polarization | - |
| Operating Temperature -10°C ~ 40°C Output Connector USB A Receptacle | Applications | ITE (Commercial) |
| Output Connector USB A Receptacle | Efficiency | Level VI, CoC Tier 2 |
| - | Operating Temperature | -10°C ~ 40°C |
| Size / Dimension 0.98" L x 1.56" W x 2.45" H (25.0mm x 39.5mm x 62.3mm) | Output Connector | USB A Receptacle |
| | Size / Dimension | 0.98" L x 1.56" W x 2.45" H (25.0mm x 39.5mm x 62.3mm) |
| Report errors? | | Report errors? |

DA10-050EU Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DA10-050EU Payment Methods



















DA10-050EU Shipping Methods













If you have any question about DA10-050EU, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com