

# DA15PF179K127

### DA15PF179K127 Information

Heisener.com	 DA15PF179K127 ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 15POS PNL MNT WW - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## DA15PF179K127 Specifications

ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesOriginal DConnector StyleD-Sub CategoryConnector TypePlug, Male PinsNumber of Positions15Number of Rows2 (DA, A)Contact TypeSignalMounting TypeSignalFlange FeatureHousing/Shell (Unthreaded)Flange FeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSojin (0.76µm)Ingress ProtectionJufu (0.76µm)Katerial Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesOriginal DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlarge FeatureGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessJup Yue YueIngress ProtectionJup YueMaterial Flammability RatingUL94 V-0	Manufacturer Part Number	DA15PF179K127
D-Sub ConnectorsPackage-SeriesOriginal DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FreminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesOriginal DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector LayoutQDA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesOriginal DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessJoµin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishJojuin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0	Series	Original D
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessJujin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureHousing/Shell (Unthreaded)TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationWire WrapFeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesGrounding IndentsShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Wire Wrap
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Grounding Indents
Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
1		Report errors?

#### DA15PF179K127 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### DA15PF179K127 Payment Methods



## DA15PF179K127 Shipping Methods



If you have any question about DA15PF179K127, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com