



DAC715P Information



For Reference Only

Part Number DAC715P

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Data Acquisition - Digital to Analog Converters

(DAC)

Description IC 16 BIT D/A CONVERTER 28-DIP

Package 28-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DAC715P Specifications

Manufacturer Part Number DAC715P Manufacturer Texas Instruments Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 28-DIP (0.300", 7.62mm) Series - Number of Bits 16 Number of D/A Converters 1 Settling Time 10µs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -		
Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 28-DIP (0.300", 7.62mm) Series - Number of Bits 16 Number of D/A Converters 1 Settling Time 10μs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	Manufacturer Part Number	DAC715P
Data Acquisition - Digital to Analog Converters (DAC)Package28-DIP (0.300", 7.62mm)Series-Number of Bits16Number of D/A Converters1Settling Time10μsOutput TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeInternalVoltage - Supply, Analog±11.4 V ~ 16.5 VVoltage - Supply, Digital-INL/DNL (LSB)±8 (Max), ±8 (Max)ArchitectureR-2ROperating Temperature-40°C ~ 85°CPackage / Case28-DIP (0.300", 7.62mm)Supplier Device Package28-PDIPMounting Type-	Manufacturer	Texas Instruments
Package 28 -DIP $(0.300", 7.62mm)$ Series-Number of Bits 16 Number of D/A Converters 1 Settling Time $10\mu s$ Output TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeInternalVoltage - Supply, Analog $\pm 11.4 \text{ V} \sim 16.5 \text{ V}$ Voltage - Supply, Digital-INL/DNL (LSB) $\pm 8 \text{ (Max)}, \pm 8 \text{ (Max)}$ ArchitectureR-2ROperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 28 -DIP $(0.300", 7.62mm)$ Supplier Device Package 28 -PDIPMounting Type-	Category	Integrated Circuits (ICs)
Series - Number of Bits 16 Number of D/A Converters 1 Settling Time 10μs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -		Data Acquisition - Digital to Analog Converters (DAC)
Number of Bits Number of D/A Converters 1 Settling Time 10µs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type - 10µs	Package	28-DIP (0.300", 7.62mm)
Number of D/A Converters Settling Time 10µs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog Voltage - Supply, Digital - INL/DNL (LSB) 48 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type - 10µs 1	Series	-
Settling Time 10µs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type -	Number of Bits	16
Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	Number of D/A Converters	1
Differential Output Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type - No No No No No Enternal **Comparation of the properation of the parallel of the par	Settling Time	10μs
Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±11.4 V ~ 16.5 V Voltage - Supply, Digital - INL/DNL (LSB) ±8 (Max), ±8 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	Output Type	Voltage - Buffered
Reference Type Internal Voltage - Supply, Analog Voltage - Supply, Digital - INL/DNL (LSB) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type - Internal Liternal Liternal	Differential Output	No
Voltage - Supply, Analog $\pm 11.4 \text{ V} \sim 16.5 \text{ V}$ Voltage - Supply, Digital - INL/DNL (LSB) $\pm 8 \text{ (Max)}, \pm 8 \text{ (Max)}$ Architecture R-2R Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	Data Interface	Parallel
Voltage - Supply, Digital- INL/DNL (LSB) ± 8 (Max), ± 8 (Max)Architecture $R-2R$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Package / Case $28-DIP$ (0.300", 7.62mm)Supplier Device Package $28-DIP$ Mounting Type-	Reference Type	Internal
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Voltage - Supply, Analog	±11.4 V ~ 16.5 V
Architecture R-2R Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	Voltage - Supply, Digital	-
Operating Temperature -40°C ~ 85°C Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	INL/DNL (LSB)	±8 (Max), ±8 (Max)
Package / Case 28-DIP (0.300", 7.62mm) Supplier Device Package 28-PDIP Mounting Type -	Architecture	R-2R
Supplier Device Package 28-PDIP Mounting Type -	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	28-DIP (0.300", 7.62mm)
	Supplier Device Package	28-PDIP
Report errors?	Mounting Type	-
Report errors:		Report errors?

DAC715P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DAC715P Payment Methods





















DAC715P Shipping Methods













If you have any question about DAC715P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com