

DAMMD3H3SJ

DAMMD3H3SJ Information

Heisener.com	 DAMMD3H3SJ ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 3POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DAMMD3H3SJ Specifications

Manufacturer Part NumberDAMMD3H3SJManufacturer QITT Cannon, LLCCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, Combo D?, D*MMConnector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMouning TypePonel Mount, Through Hole, Right AngleFlame FeatureSolderFeaturesStel, Yellow Chromate Plated ZincContact FinishStel, Yellow Chromate Plated ZincContact FinishStel, Yellow Chromate Plated ZincContact FinishStel, Yellow Chromate Plated ZincContact FinishSupin (1.27µm)Contact Finish ThicknessJuly 4V-0	_		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePowerFlange FeatureSolderFreminationSolderFeaturesSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Yo0	Manufacturer Part Number	DAMMD3H3SJ	
D-Sub ConnectorsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMoting Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC	
Package-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePonerFlange FeatureMating Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishStel Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects	
SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePowerFlange FeatureMating Side, Female Screwlock (4-40)FeaturesSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors	
Connector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureSolderFeaturesSolderFeaturesStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSoljun (1.27µm)Ingress ProtectionJ.20¥AOMaterial Flammability RatingUL94 V-0	Package	-	
Connector TypeReceptacle, Female SocketsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSojuin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, Combo D?, D*MM	
Number of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo	
Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets	
Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	3 (Power)	
Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish FinishSoljin (1.27µm)Ingress Protection-Material Flammability RatingUl94 Yol	Number of Rows	1	
Mounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A) - 3W3	
Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Power	
TerminationSolderFeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSoljin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Yellow	Mounting Type	Panel Mount, Through Hole, Right Angle	
FeaturesMounting Brackets, ShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Ye-0	Flange Feature	Mating Side, Female Screwlock (4-40)	
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder	
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Mounting Brackets, Shielded	
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc	
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold	
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50µin (1.27µm)	
	Ingress Protection	-	
Report errors?	Material Flammability Rating	UL94 V-0	
			Report errors?

DAMMD3H3SJ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DAMMD3H3SJ Payment Methods



DAMMD3H3SJ Shipping Methods



If you have any question about DAMMD3H3SJ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com