

DAMP-7X2P-J-K87

DAMP-7X2P-J-K87 Information

Heisener.com	 DAMP-7X2P-J-K87 ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 7POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DAMP-7X2P-J-K87 Specifications

Manufacturer Part NumberDAMP-7X2P-J-K87ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Schell Size, Connector Layout2 (DA, A) - 7W2Contact TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesGounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-Uuty Uuty Uuty Uuty Uuty Uuty Uuty Uuty		
CategoryConnectors, InterconnectsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector LayoutCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedForturesGoldContact FinishGoldForturesFlange Neuront, ShieldedFinish ThicknessFlashIngress Protection-Material Flamability RatingUL94 V-0	Manufacturer Part Number	DAMP-7X2P-J-K87
D-Sub ConnectorsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesStolderShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesStell Tin-Nickel PlatedShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flanmability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0	Series	Combo D?, D*M
Number of Positions7 (5 + 2 Coax)Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo
Number of Rows2Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A) - 7W2Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	7 (5 + 2 Coax)
Contact TypeCoax and SignalMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A) - 7W2
Flange FeatureBoard Side (4-40)TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Coax and Signal
TerminationSolderFeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole, Right Angle
FeaturesGrounding Indents, Mounting Brackets, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (4-40)
Shell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Grounding Indents, Mounting Brackets, Shielded
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin-Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Papart arrors	Material Flammability Rating	UL94 V-0
Report errors		Report errors?

DAMP-7X2P-J-K87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DAMP-7X2P-J-K87 Payment Methods



DAMP-7X2P-J-K87 Shipping Methods



If you have any question about DAMP-7X2P-J-K87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com