



DAR70510P Information



For Reference Only

Part Number DAR70510P Manufacturer Cynergy 3 Category Relays

Power Relays, Over 2 Amps

Description RELAY REED SPST-NO 3A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DAR70510P Specifications

Manufacturer Part Number DAR70510P Manufacturer Cynergy 3 Category Relays Power Relays, Over 2 Amps Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 178.57mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
Category Relays Power Relays, Over 2 Amps Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 178.57mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) Relays Power Relays, Over 2 Amps Power Relays Power Power Relays Power Relays Power Power Relays Power
Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 178.57mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
Package - D Relay Type Reed Coil Type Non Latching Coil Current 178.57mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current178.57mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)3ASwitching Voltage1000VAC, 1000VDC - MaxTurn On Voltage (Max)3.7 VDC
Relay TypeReedCoil TypeNon LatchingCoil Current178.57mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)3ASwitching Voltage1000VAC, 1000VDC - MaxTurn On Voltage (Max)3.7 VDC
Coil TypeNon LatchingCoil Current178.57mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)3ASwitching Voltage1000VAC, 1000VDC - MaxTurn On Voltage (Max)3.7 VDC
Coil Current 178.57mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
Contact Rating (Current) Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3A 3A Switching Voltage 1000VAC, 1000VDC - Max
Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 3.7 VDC
Turn On Voltage (Max) 3.7 VDC
• 1 1
The OCCUPATION OF THE OCCUPATI
Turn Off Voltage (Min) 0.5 VDC
Operate Time 3ms
Release Time 2ms
Features -
Mounting Type Chassis Mount
Termination Style Solder Turret
Report errors?

DAR70510P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DAR70510P Payment Methods



















DAR70510P Shipping Methods













If you have any question about DAR70510P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com