

DAT72410F

DAT72410F Information

	Part Number	DAT72410F
	Manufacturer	Cynergy 3
www.helsenge.com	Category	Relays Signal Relays, Up to 2 Amps
	Description	RELAY REED SPST-NO 2A 24V
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DAT72410F Specifications

Manufacturer Part NumberDAT72410FManufacturerCynergy 3CategoryRelaysPackage-SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mAContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn On Voltage (Max)3msRelease TimeSmsFeatures-Mounting TypeImough Hole		
CategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	facturer Part Number	DAT72410F
NetworkSignal Relays, Up to 2 AmpsPackage-SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	facturer	Cynergy 3
Package-SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)4VDCOperate Time3msRelease TimeSmsFeatures-	ory	Relays
SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-		Signal Relays, Up to 2 Amps
Relay TypeReedReidNon LachingCoil Type30.7mACoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage700VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)3msOperate TimeSmsRelease Time2msFeatures-	ge	-
Coil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-		D
Coil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	Туре	Reed
Coil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	ype	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	Current	30.7mA
Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	⁷ oltage	24VDC
Switching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	ct Form	SPST-NO (1 Form A)
Turn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	ct Rating (Current)	2A
Turn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-	ning Voltage	7000VAC, 7000VDC - Max
Operate Time3msRelease Time2msFeatures-	On Voltage (Max)	20 VDC
Release Time2msFeatures-	Off Voltage (Min)	4 VDC
Features -	te Time	3ms
	se Time	2ms
Mounting Type Through Hole	es	-
mounting Type	ting Type	Through Hole
Termination Style PC Pin, Wire Leads	nation Style	PC Pin, Wire Leads
Report		Report errors

DAT72410F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about DAT72410F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com