



DAT72410P Information



For Reference Only

Part Number DAT72410P
Manufacturer Cynergy 3
Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST-NO 2A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DAT72410P Specifications

Manufacturer Part Number Manufacturer Cynergy 3 Relays Signal Relays, Up to 2 Amps Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 30.7mA Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 2A Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type Chassis Mount Report errors?		
CategoryRelaysPackage-SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeChassis MountTermination StyleSolder Turret	Manufacturer Part Number	DAT72410P
Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 30.7mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 2A Switching Voltage 7000VAC, 7000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Chassis Mount Termination Style Solder Turret	Manufacturer	Cynergy 3
Package-SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeChassis MountTermination StyleSolder Turret	Category	Relays
SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeChassis MountTermination StyleSolder Turret		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeChassis MountTermination StyleSolder Turret	Package	-
Coil TypeNon LatchingCoil Current30.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)2ASwitching Voltage7000VAC, 7000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeChassis MountTermination StyleSolder Turret	Series	D
Coil Current 30.7mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 2A Switching Voltage 7000VAC, 7000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Chassis Mount Termination Style Solder Turret	Relay Type	Reed
Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 2A Switching Voltage 7000VAC, 7000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 3ms Release Time 2ms Features	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 2A Switching Voltage 7000VAC, 7000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Chassis Mount Termination Style Solder Turret	Coil Current	30.7mA
Contact Rating (Current) Switching Voltage 7000VAC, 7000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Chassis Mount Termination Style	Coil Voltage	24VDC
Switching Voltage 7000VAC, 7000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Chassis Mount Termination Style Solder Turret	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 2ms Features - Mounting Type Chassis Mount Termination Style 20 VDC 4 VDC 3ms - Chassis Mount Solder Turret	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 3ms Release Time 2ms Features - Mounting Type Chassis Mount Termination Style A VDC Onerate Time Chassis Mount Solder Turret	Switching Voltage	7000VAC, 7000VDC - Max
Operate Time3msRelease Time2msFeatures-Mounting TypeChassis MountTermination StyleSolder Turret	Turn On Voltage (Max)	20 VDC
Release Time 2ms Features - Mounting Type Chassis Mount Termination Style Solder Turret	Turn Off Voltage (Min)	4 VDC
Features - Mounting Type Chassis Mount Termination Style Solder Turret	Operate Time	3ms
Mounting Type Chassis Mount Termination Style Solder Turret	Release Time	2ms
Termination Style Solder Turret	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Turret
		Report errors?

DAT72410P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DAT72410P Payment Methods



















DAT72410P Shipping Methods













If you have any question about DAT72410P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com