

# **DBM-25S-E**

#### **DBM-25S-E Information**

| Contact service class been | <br>DBM-25S-E<br>ITT Cannon, LLC<br>Connectors, Interconnects<br>D-Sub Connectors<br>CONN D-SUB RCPT 25P PNL MNT SLDR<br>-<br>For the pricing/inventory/lead time, please contact |                 |
|----------------------------|---|-----------------|
| For Reference Only         | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com   | Request a Quote |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **DBM-25S-E Specifications**

| ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesD*MConnector StyleD-Sub ConnectorsConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeJolderFlange FeatureSolderFeatures-Shell Material, FinishStell, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashAuger SprotectionFlashMaterial Flammability RatingU49 V-0        |                              |                                    |
|---|------------------------------|------------------------------------|
| CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Shell Size, Connector LayoutG(DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Manufacturer Part Number     | DBM-25S-E                          |
| D-Sub ConnectorsPackage-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypePanel Mount, Through HoleMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Manufacturer                 | ITT Cannon, LLC                    |
| Package-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFreminationSolderShell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0   | Category                     | Connectors, Interconnects          |
| SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0   |                              | D-Sub Connectors                   |
| Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0   | Package                      | -                                  |
| Connector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Series                       | D*M                                |
| Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0   | Connector Style              | D-Sub                              |
| Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Connector Type               | Receptacle, Female Sockets         |
| Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0  | Number of Positions          | 25                                 |
| Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 Yellow   | Number of Rows               | 2                                  |
| Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Shell Size, Connector Layout | 3 (DB, B)                          |
| Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 Yellow   | Contact Type                 | Signal                             |
| TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Mounting Type                | Panel Mount, Through Hole          |
| Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 Yellow Chromate Material  | Flange Feature               | Housing/Shell (Unthreaded)         |
| Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Termination                  | Solder                             |
| Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Features                     | -                                  |
| Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0  | Shell Material, Finish       | Steel, Yellow Chromate Plated Zinc |
| Ingress Protection-Material Flammability RatingUL94 V-0   | Contact Finish               | Gold                               |
| Material Flammability Rating UL94 V-0   | Contact Finish Thickness     | Flash                              |
|   | Ingress Protection           | -                                  |
| Report errors?  | Material Flammability Rating | UL94 V-0                           |
| 1   |                              | Report errors?                     |

#### **DBM-25S-E** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DBM-25S-E, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com