



#### **DBMM17X2SM Information**

Heisener.com

Part Number DBMM17X2SM Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**D-Sub Connectors** 

**Description** CONN D-SUB RCPT 17P PNL MNT SLDR

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DBMM17X2SM Specifications**

Manufacturer Part NumberDBMM17X2SMManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0Report errors?	•	
Category  Connectors, Interconnects  D-Sub Connectors  Package  - Series  MIL-DTL-24308, Combo D?, D*MM  Connector Style  D-Sub, Combo  Receptacle, Female Sockets  Number of Positions  17 (15 + 2 Coax)  Number of Rows  2  Shell Size, Connector Layout  Contact Type  Coax and Signal  Mounting Type  Panel Mount, Through Hole  Flange Feature  Housing/Shell (Unthreaded)  Termination  Solder  Features  Shielded  Shell Material, Finish  Steel, Yellow Chromate Plated Zinc  Contact Finish Thickness  50µin (1.27µm)  Ingress Protection  - Material Flammability Rating  UL94 V-0	Manufacturer Part Number	DBMM17X2SM
Package - Series MIL-DTL-24308, Combo D?, D*MM Connector Style D-Sub, Combo Connector Type Receptacle, Female Sockets Number of Positions 17 (15 + 2 Coax) Number of Rows 2 Shell Size, Connector Layout 3 (DB, B) - 17W2 Contact Type Coax and Signal Mounting Type Panel Mount, Through Hole Flange Feature Housing/Shell (Unthreaded) Termination Solder Features Shielded Shell Material, Finish Steel, Yellow Chromate Plated Zinc Contact Finish Thickness 50µin (1.27µm) Ingress Protection Material Flammability Rating UL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
Series MIL-DTL-24308, Combo D?, D*MM  Connector Style D-Sub, Combo  Connector Type Receptacle, Female Sockets  Number of Positions 17 (15 + 2 Coax)  Number of Rows 2  Shell Size, Connector Layout 3 (DB, B) - 17W2  Contact Type Coax and Signal  Mounting Type Panel Mount, Through Hole  Flange Feature Housing/Shell (Unthreaded)  Termination Solder  Features Shielded  Shell Material, Finish Steel, Yellow Chromate Plated Zinc  Contact Finish Thickness 50µin (1.27µm)  Ingress Protection -  Material Flammability Rating UL94 V-0		D-Sub Connectors
Connector Style Connector Type Receptacle, Female Sockets Number of Positions 17 (15 + 2 Coax) Number of Rows 2 Shell Size, Connector Layout 3 (DB, B) - 17W2 Contact Type Coax and Signal Mounting Type Panel Mount, Through Hole Flange Feature Housing/Shell (Unthreaded) Termination Solder Features Shielded Shell Material, Finish Steel, Yellow Chromate Plated Zinc Contact Finish Thickness Ingress Protection - Material Flammability Rating UL94 V-0	Package	-
Connector Type Receptacle, Female Sockets  Number of Positions 17 (15 + 2 Coax)  Number of Rows 2  Shell Size, Connector Layout 3 (DB, B) - 17W2  Contact Type Coax and Signal  Mounting Type Panel Mount, Through Hole  Flange Feature Housing/Shell (Unthreaded)  Termination Solder  Features Shielded  Shell Material, Finish Steel, Yellow Chromate Plated Zinc  Contact Finish Thickness 50µin (1.27µm)  Ingress Protection -  Material Flammability Rating UL94 V-0	Series	MIL-DTL-24308, Combo D?, D*MM
Number of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo
Number of Rows  Shell Size, Connector Layout  Contact Type  Coax and Signal  Mounting Type  Panel Mount, Through Hole  Flange Feature  Housing/Shell (Unthreaded)  Termination  Solder  Features  Shielded  Shell Material, Finish  Steel, Yellow Chromate Plated Zinc  Contact Finish Thickness  50µin (1.27µm)  Ingress Protection  Material Flammability Rating  UL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout  Contact Type  Coax and Signal  Mounting Type  Panel Mount, Through Hole  Flange Feature  Housing/Shell (Unthreaded)  Termination  Solder  Features  Shielded  Shell Material, Finish  Steel, Yellow Chromate Plated Zinc  Contact Finish  Gold  Contact Finish Thickness  50µin (1.27µm)  Ingress Protection  Material Flammability Rating  UL94 V-0	Number of Positions	17 (15 + 2 Coax)
Contact Type  Mounting Type  Panel Mount, Through Hole  Flange Feature  Housing/Shell (Unthreaded)  Termination  Solder  Features  Shielded  Shell Material, Finish  Steel, Yellow Chromate Plated Zinc  Contact Finish Thickness  50µin (1.27µm)  Ingress Protection  Material Flammability Rating  UL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B) - 17W2
Flange Feature Housing/Shell (Unthreaded)  Termination Solder  Features Shielded  Shell Material, Finish Steel, Yellow Chromate Plated Zinc  Contact Finish Gold  Contact Finish Thickness 50µin (1.27µm)  Ingress Protection -  Material Flammability Rating UL94 V-0	Contact Type	Coax and Signal
TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Shielded
Contact Finish Thickness 50μin (1.27μm)  Ingress Protection -  Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50μin (1.27μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### **DBMM17X2SM Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **DBMM17X2SM Payment Methods**



















### **DBMM17X2SM Shipping Methods**













If you have any question about DBMM17X2SM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com