

DBMM25PA101

uest a Quote

DBMM25PA101 Information

Heisener.com	Part Number	DBMM25PA101
	Manufacturer	ITT Cannon, LLC
	Category	Connectors, Interconnects D-Sub Connectors
	Description	CONN D-SUB PLUG 25POS PNL MNT
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DBMM25PA101 Specifications

SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSpin (1.27µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSipin (1.27µm)Ingress ProtectionJ.27µm)Ingress ProtectionU.94 V-0	Manufacturer Part Number	DBMM25PA101
D-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypePanel MountMunting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions2Number of Rows3 (DB, B)Contact TypeSignalContact TypePanel MountMunting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness-Metrial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishSolyin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, D*MM
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Ye-0	Number of Rows	2
Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSolµin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Ye-0	Mounting Type	Panel Mount
Features-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder Cup
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Cadmium
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50μin (1.27μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors

DBMM25PA101 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DBMM25PA101 Payment Methods



DBMM25PA101 Shipping Methods



If you have any question about DBMM25PA101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com