

DBMMF17W2S

DBMMF17W2S Information

| Heisener.com | DBMMF17W2S ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 17POS PNL MNT - For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DBMMF17W2S Specifications

| Manufacturer Part NumberDBMMF17W2SManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector LayoutSignal and Coax or Power (Not Included)Flange FeatureHousing/Shell (Unthreaded)Flange FeaturesSolder CupForturesSolder CupForturesSielel Material, FinishContact FinishGoldContact Finish ThicknessSoly in (1.27µm)Ingress Protection-Layout Current Part PartPart PartMauntiari Hammability RatingDuny HouContact Finish ThicknesSoly in (1.27µm)Ingress Protection-Part PartPart PartMartiari FinishSoly in (1.27µm)Ingress Protection-Part PartPart PartPart PartPart PartPart Part-Part Part-Part Part Part-Part Part Part-Part Part Part Part-Part Part Part Part-Part Part Part Part Part Part Part Part | _ | | |
|---|------------------------------|---|----------------|
| CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Panel Mounting TypePanel MountFlange FeatureSolder CupFeaturesSolder CupFeaturesSieleldShell Material, FinishSteel, Yellow Chromate Plated ZincContact TipishGoldContact FinishSoljen (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Manufacturer Part Number | DBMMF17W2S | |
| D-Sub ConnectorsPackage-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)FeaturesSider CupShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness5/pin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Manufacturer | ITT Cannon, LLC | |
| Package-SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeBignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)FeaturesSider CupShell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessJojin (127µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Category | Connectors, Interconnects | |
| SeriesMIL-DTL-24308, Combo D?, D*MMConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)FeaturesSolder CupShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness5 Jojin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | | D-Sub Connectors | |
| Connector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)FeaturesSolder CupFeaturesShelleddShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Package | - | |
| Connector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShelledShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Series | MIL-DTL-24308, Combo D?, D*MM | |
| Number of Positions17 (15 + 2 Coax or Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Connector Style | D-Sub, Combo | |
| Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Connector Type | Receptacle, Female Sockets | |
| Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShell Adterial, FinishShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessSoljari (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Number of Positions | 17 (15 + 2 Coax or Power) | |
| Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShell dedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Number of Rows | 2 | |
| Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Shell Size, Connector Layout | 3 (DB, B) - 17W2 | |
| Flange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Contact Type | Signal and Coax or Power (Not Included) | |
| TerminationSolder CupFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Mounting Type | Panel Mount | |
| FeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Flange Feature | Housing/Shell (Unthreaded) | |
| Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Termination | Solder Cup | |
| Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Features | Shielded | |
| Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0 | Shell Material, Finish | Steel, Yellow Chromate Plated Zinc | |
| Ingress Protection - Material Flammability Rating UL94 V-0 | Contact Finish | Gold | |
| Material Flammability Rating UL94 V-0 | Contact Finish Thickness | 50μin (1.27μm) | |
| | Ingress Protection | - | |
| Papart errors? | Material Flammability Rating | UL94 V-0 | |
| Report enois: | | R | Report errors? |

DBMMF17W2S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DBMMF17W2S Payment Methods



DBMMF17W2S Shipping Methods



If you have any question about DBMMF17W2S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com