

# DBMN13H3SNA197

#### **DBMN13H3SNA197** Information

Contraction term	DBMN13H3SNA197 ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 13P PNL MNT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **DBMN13H3SNA197** Specifications

ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypePanel Mount, Through HoleHange FeatureMating Side, Female Screwlock (4-40)Flange FeaturesSodlerFeaturesGoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-		
CategoryConnectors, InterconnectsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector LayoutSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DBMN13H3SNA197
Package-SeriesCombo D?, D*MConnector StyleD-Sub ComboConnector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0	Series	Combo D?, D*M
Number of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo
Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	13 (10 + 3 Power)
Contact TypeSignal and PowerMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B) - 13C3, 13W3
Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal and Power
TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Shielded
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin-Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### **DBMN13H3SNA197** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# DBMN13H3SNA197 Payment Methods



#### DBMN13H3SNA197 Shipping Methods



If you have any question about DBMN13H3SNA197, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com