

DBMN17C2SNA197

DBMN17C2SNA197 Information

Contract levels and they	 DBMN17C2SNA197 ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 17P PNL MNT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DBMN17C2SNA197 Specifications

ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-		
CategoryConnectors, InterconnectsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector LayoutGoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DBMN17C2SNA197
Package-SeriesCombo D?, D*MConnector StyleD-Sub ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoalContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0	Series	Combo D?, D*M
Number of Positions17 (15 + 2 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo
Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	17 (15 + 2 Coax)
Contact TypeCoax and SignalMounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B) - 17W2
Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Coax and Signal
TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Shielded
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin-Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DBMN17C2SNA197 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

DBMN17C2SNA197 Payment Methods



DBMN17C2SNA197 Shipping Methods



If you have any question about DBMN17C2SNA197, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com