

# DBO13W3P700G30LF

#### DBO13W3P700G30LF Information

| Heisener.com       | DBO13W3P700G30LF<br>Amphenol FCI<br>Connectors, Interconnects<br>D-Sub Connectors<br>CONN D-SUB PLUG 13POS R/A SOLDER<br>-<br>For the pricing/inventory/lead time, please contact |           |
|--------------------|---|-----------|
| For Reference Only | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com   | Request a |

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Quote

## DBO13W3P700G30LF Specifications

| Manufacturer Part NumberDB013W3P700G30LFManufacturerAmphenol FCICategoryConnectors, InterconnectsDasub ConnectorsD-Sub ConnectorsPackage-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Contact Finish Thickness-Co |                              |  |
|--|------------------------------|--|
| CategoryConnectorsCategoryConnectorsPackage-SeriesDWConnector StyleD-Sub ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishStele, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Manufacturer Part Number     | DBO13W3P700G30LF                                 |
| PackageD-Sub ConnectorsPackage-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishStell, Tin PlatedContact Finish Thickness-Ingress Protection-Metrial Flammability RatingUL94 V-0   | Manufacturer                 | Amphenol FCI                                     |
| Package-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Metrial Flammability RatingUL94 V-0   | Category                     | Connectors, Interconnects                        |
| SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Sciel (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0   |                              | D-Sub Connectors                                 |
| Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Package                      | -  |
| Connector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishGoldContact Finish Thickness-Ingress Protection-Material Flamability RatingUL94 V-0  | Series                       | DW   |
| Number of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0   | Connector Style              | D-Sub, Combo                                     |
| Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0   | Connector Type               | Plug, Male Pins                                  |
| Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Number of Positions          | 13 (10 + 3 Power)                                |
| Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Number of Rows               | 2  |
| Mounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Shell Size, Connector Layout | 3 (DB, B) - 13C3, 13W3                           |
| Flange FeatureBoard Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Contact Type                 | Signal and Power                                 |
| TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0   | Mounting Type                | Through Hole, Right Angle                        |
| FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Flange Feature               | Board Side (4-40)                                |
| Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0  | Termination                  | Solder   |
| Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0   | Features                     | Board Lock, Grounding Indents, Mounting Brackets |
| Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0   | Shell Material, Finish       | Steel, Tin Plated                                |
| Ingress Protection-Material Flammability RatingUL94 V-0  | Contact Finish               | Gold   |
| Material Flammability Rating UL94 V-0  | Contact Finish Thickness     | -  |
|  | Ingress Protection           | -  |
|  | Material Flammability Rating | UL94 V-0   |
| Report errors?   |                              | Report errors?                                   |

#### DBO13W3P700G30LF Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### DBO13W3P700G30LF Payment Methods



If you have any question about DBO13W3P700G30LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com